



# Material Safety Data Sheet NAIL PREP

## Section 1 – Identification

**Product Name:** NAIL PREP

**Chemical Name:** N/A

**Family:** Cleansing Agent  
**Product Use:** Nail Primer

**PRODUCT #:**  
**NAIL PREP**

**Manufacturer:** NAILITE

4530 N HIATUS ROAD #109 SUNRISE, FL 33351

**Information Contacts:** (954) 741-2924

**Emergency Phone Numbers:** US & Canada (954)741-2924

**Emergency Phone Numbers:** International: 1-352-323-3500

## Section 2 – Hazards Identification

### EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- **Flammable liquid and vapor!**
- May cause eye irritation.
- May cause skin irritation.
- Avoid prolonged or repeated breathing of gases, vapors or mists.
- Please read entire MSDS for additional information.



### Potential Health Effects, Signs and Symptoms of Exposure:

**Primary Route of Entry** Inhalation, skin and ingestion.

**Eye** Vapors are irritating to the eyes. Splashes may cause severe irritation, with stinging, tearing, redness, and pain with possible corneal damage.

**Skin** Repeated/prolonged contact may cause drying of skin. Symptoms include redness, burning, drying, cracking and skin burns.

**Ingestion** Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.

**Inhalation** Vapors are irritating to nasal passages and throat and may cause stupor or headache. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

**Sub-Chronic Effects** Significant exposure to this chemical may adversely affect people with chronic disease or may cause damage to the respiratory system, skin and eyes.

NOTE: Refer to Section 11, Toxicological Information for Details

## Section 3 – Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure OSHA	Limits ACGIH	Carcinogen	%
				TWA/STEL	TWA/STEL		
Isopropyl Alcohol	67-63-0	200-661-7	Isopropyl Alcohol	400 ppm	400 ppm	Not Listed	40-50
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400 ppm	400 ppm	Not Listed	30-40
Isobutyl Acetate	110-19-0	203-745-1	Isobutyl Acetate	150 ppm	150 ppm	Not Listed	10-20

N/E – None Established N/DA – No Data Available

N/R – Not Reviewed N/A – Not Applicable

**Isopropyl Alcohol:** Hazard Symbol – F, Xi Risk Phrases – R11, R36, R67 Safety Phrases – S2, S7, S16, S24/25, S26

**Ethyl Acetate:** Hazard Symbol – F, Xi Risk Phrases – R 11, R36, R66, R67 Safety Phrases – S2, S16, S26, S33

**Isobutyl Acetate:** Hazard Symbol – F Risk Phrases – R11, R66 Safety Phrases – S2, S16, S23, S25, S29, S33

See Section 16 for Risk and Safety Phrase Key

## Section 4 – First Aid Measures

**First Aid for Eye** Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.

**First Aid for Skin** Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.

**First Aid for Ingestion** If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**First Aid for Inhalation** Remove to fresh air. If having breathing difficulty, give oxygen. If breathing has stopped, give artificial respiration. Seek medical attention if discomfort persists.

**Material Safety Data Sheet**      **NAIL PREP****Section 5 – Fire Fighting Measures**

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
68°F/20°C	LEL: 2 % ; UEL: 11.4 %	N/DA

**Method:**

Extinguishing Media:	Use CO <sub>2</sub> , dry chemical for small fires, or alcohol type aqueous film forming foam.
Fire Fighting Instructions:	If potential for exposure to vapors or products of combustion, wear complete personal protective equipment including self contained breathing apparatus, with full face operated in pressure demand. Fight fire from a safe distance/protected location.
Unusual Hazards:	Flammable. When exposed to heat and flame, material is a fire explosion hazard. Vapor is heavier than air and can travel considerable distance to source of ignition and flash back. Material creates a special hazard if it floats on water.

**Section 6 – Accidental Release Measures**

Spill or Release Procedures	Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.
-----------------------------	---

**Section 7 – Handling and Storage**

Handling	Closed containers exposed to temperature above (120 ° F) in transit or storage may develop vapor pressure. Open containers slowly. Ground all metal containers when transferring material. Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking.
Storage	Store in a cool, well ventilated area away from heat, sparks and flame. Keep containers closed when not in use.
Explosion Hazard	Flammable liquid. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**Section 8 – Exposure Controls / Personal Protection**

Engineering Controls	Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.
----------------------	---

**Personal Protective Equipment**

General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/ Face Protection	Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses.
Skin Protection	Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Neoprene and Nitrile rubber is better than PVC.
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-face piece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

# Material Safety Data Sheet NAIL PREP

## Section 9 – Physical and Chemical Properties

Appearance	Odor & Odor Threshold	H P	VOC (g/L)	Specific Gravity	Viscosity	% Volatile	
Clear, colorless, mobile liquid	fruity, pungent mix odor	N/A	920	(H20=1): 0.92	N/A	W/W % : 99+	
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
77°C	N/DA	N/DA	73 mm Hg @20°C	(Air=1): 3.0	(Butyl Acetate=1): 4.5	N/A	8.7 %
Flash Point(°F/°C)		Flammable Limit (vol%)		Auto-ignition Temperature (vol%)			
68°F/20°C		LEL: 2 % ; UEL: 11.4 %		N/DA			

## Section 10 – Stability and Reactivity

<b>Stability:</b> Stable	<b>Incompatibility (Materials to Avoid):</b> Oxidizing Agent i.e. Hydrogen peroxide, Nitric Acid, Perchloric Acid, Chromium Trioxide
<b>Hazardous Decomposition Products:</b> Carbon Monoxide	<b>Hazardous Polymerization:</b> Will not occur
<b>Conditions to Avoid:</b> Heat, flames, ignition sources, and incompatibles	

## Section 11 – Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation – skin	Irritation – Eye
Mouse: LD50 = 3600 mg/kg;	N/ DA	Rat = 1030 ug/m3/16W	Skin, rabbit: LD50 = 12800 mg/kg.	N/ DA
Sensitization		Mutagenicity		Sub-chronic Toxicity
N/ DA		Rat = 1030 ug/m3/16W		N/ DA

## Section 12 – Ecological Information

### Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
The LC50/96-hour values for fish are over 100 mg/l.	N/ DA	N/ DA	N/ DA	N/ DA

### Chemical Fate Information

<b>Biodegradability</b>	When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released to water, this material is expected to quickly evaporate. When released into the water, this material is expected to have a half-life between 1 and 10 days. When released into water, this material may biodegrade to a moderate extent. This material is not expected to significantly bioaccumulate.
<b>Chemical Oxygen Demand</b>	N/ DA

## Section 13 – Disposal Considerations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

# Material Safety Data Sheet NAIL PREP

## Section 14 – Transport Information

<b>DOT (49 CFR 172)</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PGII
Identification Number:	UN1993
Marine Pollutant:	No
Special Provisions:	T8, T31
<b>Emergency Response Guidebook (ERG) #:</b>	<b>128</b>
<b>IATA (DGR):</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PGII
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	
<b>Emergency Response Guidance (ICAO)#:</b>	
<b>IMO (IMDG):</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PGII
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation:	None
<b>Emergency Schedule (EmS)#:</b>	
<b>Other Information:</b>	<b>Flash point = 20°C</b>

## Section 15 – Regulatory Information

### US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following HAP's or ODS: <ul style="list-style-type: none"> <li>NONE</li> </ul>
Clean Water Act: Priority Pollutant	The following ingredients are listed as hazardous pollutants under the CWA: <ul style="list-style-type: none"> <li>Isobutyl Acetate, CAS# 110-19-0</li> </ul> None of the ingredients are listed as primary pollutants nor are they listed as toxic pollutants.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food-packaging additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. It's hazards are: <ul style="list-style-type: none"> <li>Immediate (acute) health hazard</li> <li>Fire hazard</li> </ul>
RCRA	This product contains the following chemicals considered to be hazardous waste under RCRA (40 CFR 261). <ul style="list-style-type: none"> <li>Ethyl Acetate CAS# 141-78-6, RCRA Code: U112</li> <li>Characteristic of Ignitability, RCRA Code: D001</li> </ul>
SARA Title III: Section 302	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA Title III: Section 304	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERC LA" List): <ul style="list-style-type: none"> <li>Ethyl Acetate CAS# 141-78-6, RQ (Lbs) 5000</li> <li>Isobutyl Acetate CAS# 110-19-0, RQ (Lbs) 5000.</li> </ul>
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). It's hazards are: <ul style="list-style-type: none"> <li>Immediate (acute) health hazard</li> <li>Fire hazard</li> </ul>
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> <li>Isopropyl Alcohol CAS# 67-63-0</li> </ul>
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.

### State Regulations

CA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Isobutyl Acetate CAS #110-19-0.
-----------------------	--


# Material Safety Data Sheet NAIL PREP

California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS #67-63-0, Isobutyl Acetate CAS #110-19-0.
NJ Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS #67-63-0, Isobutyl Acetate CAS #110-19-0.
PA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS #67-63-0, Isobutyl Acetate CAS #110-19-0.
FL Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS #67-63-0, Isobutyl Acetate CAS #110-19-0.
MN Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS #67-63-0, Isobutyl Acetate CAS #110-19-0.

**International Regulations**

CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS #67-63-0, Isobutyl Acetate CAS #110-19-0.
--	--

**Labeling according to EC Directives – 1999/45/EC**



<p>European Community:</p> 	<p><b>Nail Prep:</b></p> <ul style="list-style-type: none"> <li>HAZARD SYMBOLS: <b>Xn, F:</b> Harmful, Highly Flammable</li> <li>RISK PHRASES: <b>R11,</b> highly flammable, <b>R20/22:</b> Harmful by inhalation and if swallowed, <b>R36/37/38:</b> Irritating to eyes, respiratory system and skin</li> <li>SAFETY PHRASES: <b>S7/9:</b> keep container tightly closed and in a well ventilated place, <b>S16:</b> keep away from sources of ignition- no smoking, <b>S24/25:</b> avoid contact with skin and eyes, <b>S33:</b> take precautionary measures against static discharges, <b>S37/39:</b> wear suitable gloves and eye/face protection, <b>S45:</b> In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)</li> </ul>
--	--

**Section 16 – Other Information**

**EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):**

<p><b>Hazard Symbol:</b>                  F – Flammable substances or preparations                  Xi – Irritants</p> <p><b>Risk Phrases:</b>                  R11 – Highly flammable; R36 – Irritating to eyes; R66 – Repeated exposure may cause skin dryness or cracking; R67 – Vapors may cause drowsiness and dizziness</p> <p><b>Safety Phrases:</b>                  S2 Keep out of the reach of children; S7 Keep container tightly closed; S16 Keep away from sources of ignition – No smoking; S23 Do not breathe gas/fumes/vapor/spray S24/25 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice                  S29 Do not empty into drains; S33 Take precautionary measures against static discharges</p>
---

**Hazard Rating System (Pictograms)**

<p><b>NFPA:</b></p> 	<p><b>HMIS:</b></p> 
---	---

MSDS Prepared by:	BSQ
-------------------	-----

Revision History:	10/29/04 Section 2 % changed from <, > to range, headers changed, format update
	12/20/07 DOT Name update
	09/18/08 Updated section 16
	10/22/08 Updated Format
	11/04/08 Updated Risk and Safety Phrases

**Material Safety Data Sheet**      **NAIL PREP**

	12/10/08 Updated specific gravity and VOC
	03/16/08 Updated to meet Globally Harmonized System requirements. Added the EU address to section 1. Switched location of section 2 with section 3. Changed the title in sections 1, 8, and 13. Moved MSDS preparation to section 16.
	02/05/10 Added international emergency phone number to section 1

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

Nailite components are provided on an as is basis without warranties of any kind either expressed or implied. Nailite does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said Nailite components.