

NAILITE
QUICK DRY OIL

SAFETY
DATA SHEET

REVISED EDITION: 1
DATE: 04/07/2011
SUPERSEDED: 0/0/0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

TRADE NAME: QUICK DRY OIL
IDENTIFICATION OF PRODUCT: BLUE LIQUID
TYPE OF PRODUCT: MINERAL OIL
USE: FOR PROFESSIONAL USE ONLY
COMPANY IDENTIFICATION: NAILITE 4530 N HIATUS ROAD #109 SUNRISE, FL 33351 USA
EMERGENCY NUMBER: INFOTRAC 352-323-3500

2. HAZARDS IDENTIFICATION

SYMPTOMS RELATED TO USE:

INHALATION: BREATHING HIGH CONCENTRATIONS OF VAPORS MISTS MAY CAUSE IRRITATION OF THE NOSE AND THROAT. SIGNS OF NERVOUS SYSTEM DEPRESSION.
SKIN: THIS PRODUCT MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED EXPOSURE TO THIS MATERIAL MAY CAUSE REDNESS AND BURNING, DRYING AND CRACKING OF DERMATITIS.
EYES: THIS PRODUCT MAY CAUSE EYE IRRITATION. DIRECT CONTACT WITH THIS MATERIAL OR EXPOSURE TO ITS VAPORS OR MISTS (GREATER THAN APPROX. 1000 ppm) MAY CAUSE BURING, TEARING, REDNESS AND SWELLING.
INGESTION: INGESTION OF EXCESSIVE QUANTITIES MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT. SIGNS OF NERVOUS SYSTEM DEPRESSION.

3. COMPOSTION/INFORMATION OF INGREDIENTS

<u>REPORTABLE COMPONENTS</u>	<u>CAS NUMBER</u>	<u>WEIGHT/PERCENT</u>
MINERAL OIL	8012-95-1	40.0%-50.0%
MINERAL SPIRITS 500 ppm (TWA)	8052-41-3	40.0%-50.0%
ETHYL ACETATE TLV/PEL: 400 ppm	141-78-6	1.0%

4. FIRST AID MEASURES

INHALATION: IN CASE OF IRRITATION BY VAPOR, REMOVE FROM EXPOSURE, TREAT SYMPTOMS AND GET MEDICAL ATTENTION IF SYMPTOMS PERSISTS.
EYES: ANY MATERIAL THAT CONTACTS THE EYE SHOULS BE WASHED OUT IMMEDIATELY AND MEDICAL ATTENTION OBTAINED IF SYMPTOMS PERSIST.
SKIN: WASH WITH SOAP AND PLENTY OF WATER.
INGESTION: CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. INDUCE VOMITING AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PEROSN.

NAILITE
4530 N HIATUS ROAD #109
SUNRISE, FL 33351 UNITED STATES
800-222-4472/954-741-2924

IN CASE OF EMERGENCY: 1-352-323-3500

NAILITE
QUICK DRY OIL

SAFETY
DATA SHEET

REVISED EDITION: 1
DATE: 04/07/2011
SUPERSEDED: 0/0/0

5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

WATER IS THE MOST EFFECTIVE FIRE EXTINGUISHING MEDIUM. IT IS RECOMMENDED TO BE USED IN LARGE VOLUME. DRY CHEMICAL, CO2 OR A UNIVERSAL TYPE FOAM COULD BE USED TO EXTINGUISH SMALL FIRES. **SPECIAL FIREFIGHTING PROCEDURES:**

WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. **UNUSUAL FIRE AND EXPLOSION HAZARDS:** MATERIAL IS FLAMMABLE. VAPORS MAY TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP AWAY FROM HEAT, SPARKS, FLAME. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION.

6 ACCIDENTAL RELEASE MEASURES

STAY UPWIND AND AWAY FROM SPILL. KEEP ALL SOURCES OF IGNITION AND HOT METAL SURFACES AWAY FROM SPILL. KEEP OUT OF DRAINS, SEWERS OR WATERWAYS. USE SAND OR OTHER INERT MATERIALS TO DAM AND CONTAIN SPILL. DO NOT FLUSH WITH WATER; USE ABSORBANT PADS. FOR LARGE SPILLS CALL RESPONSE TEAM AND NOTIFY APPROPRIATE STATE/LOCAL AGENCIES. IMMEDIATELY NOTIFY THE NATIONAL RESPONSE CENTER IN CASE IF THE SPILL IS IN EXCESS OF EPA REPORTABLE QUANTITY.

WASTE DISPOSAL METHOD: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

7 HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: USE NON-SPARKING UTENSILS WHEN HANDLING THIS MATERIAL. KEEP CONTAINERS TIGHTLY CLOSED, COOL AND DRY AND AWAY FROM SOURCES OF IGNITION.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: WHEN VAPOR CONCENTRATION EXCEEDS THE ESTABLISHED EXPOSURE LIMITS RESPIRATORY PROTECTION IS NECESSARY. DEPENDING ON THE AIRBORNE CONCENTRATION, USE A RESPIRATOR OR GAS MASK WITH APPROPRIATE CARTRIDGES AND CANISTERS OR SUPPLIED AIR EQUIPMENT.

VENTILATION: THE VENTILATION SYSTEM SHOULD BE DESIGNED TO BE ABLE TO MAINTAIN AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS. IF THE CURRENT VENTILATION IS NOT ADEQUATE TO MAINTAIN THIS LEVEL, ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED. USE EXPLOSION PROOF EQUIPMENT.

PROTECTIVE GLOVES: THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES) ARE RECOMMENDED FOR ANY TYPE OF INDUSTRIAL CHEMICAL HANDLING.

OTHER: THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION. USE SPLASH GOGGLES TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

NAILITE

4530 N HIATUS ROAD #109
SUNRISE, FL 33351 UNITED STATES
800-222-4472/954-741-2924
800-222-4472/954-741-2924

IN CASE OF EMERGENCY: 1-352-323-3500

NAILITE
QUICK DRY OIL

SAFETY
DATA SHEET

REVISED EDITION: 1
DATE: 04/07/2011
SUPERSEDED: 0/0/0

9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: 78C-330C
VAPOR DENSITY: COATING V.O.C.:0.0 LB/G
SOLUBILITY IN WATER: INSOLUBLE
APPEARANCE AND ODOR: TRANSPARENT BLUE TINT OIL, NO ODOR
SPECIFIC GRAVITY: (H2O=1): .794
EVAPORATION RATE: MATERIAL V.O.C.:0.0 LB/G
FLASH POINT: 24F
METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME-LOWER:0.5 UPPER 12.7

10 STABILITY AND REACTIVITY

STABILITY: STABLE
CONDITONS TO AVOID: FLAME, ELECTRIC SPARK, STATIC AND HEAT
INCOMPATIBILITY (MATERIALS TO AVOID): THIS PRODUCT IS INCOMPATIBLE WITH STRONG ACIDS OR BASES AND OXIDIZERS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE, CARBON DIOXIDE AND NITROGEN OXIDE. UNDER SOME CONDITIONS, METHANE, IRRITATING ALDEHYDES AND CARBOXYLIC ACIDS AND HYDROGEN CYANIDE MAY BE FORMED.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

11 TOXICOLOGICAL INFORMATION

NO INFORMATION AVAILABLE

12 ECOLOGICAL INFORMATION

NO INFORMATION AVAILABLE

NAILITE
4530 N HIATUS ROAD #109
SUNRISE, FL 33351 UNITED STATES
800-222-4472/954-741-2924
800-222-4472/954-741-2924

IN CASE OF EMERGENCY: 1-352-323-3500

NAILITE
QUICK DRY OIL

SAFETY
DATA SHEET

REVISED EDITION: 1
DATE: 04/07/2011
SUPERSEDED: 0/0/0

13 DISPOSAL CONSIDERATIONS

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

14 TRANSPORT INFORMATION

PROPER SHIPPING NAME: UN 1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE SOLUTION), CLASS 3, PG II

UN NO: 1993

LABELING ADR:



15 REGULATORY INFORMATION

SYMBOLS: Xn: HARMFUL
F: HIGHLY FLAMMABLE

R PHRASE (S): R11: HIGHLY FLAMMABLE
R20/21/22: HARMFUL BY INHALATION IN CONTACT WITH SKIN AND IF SWALLOWED
R33: DANGER OF CUMULATIVE EFFECTS
R36/37/38: IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN
R43: MAY CAUSE SENSITIZATION BY SKIN CONTACT

S PHRASE (S): S3: KEEP IN A COOL PLACE
S9: KEEP CONTAINER IN A WELL-VENTILATED PLACE
S16: KEEP CONTAINER IN A WELL VENTILATED PLACE
S24: AVOID CONTACT WITH SKIN
S26: IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE
S33: TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES
S35: THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF IN A SAFE WAY
S36/37: WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES
S43: IN CASE OF FIRE USE
S51: USE ONLY IN A WELL-VENTILATED AREA
S59: REFER TO MANUFACTURER/SUPPLIER FOR INFORMATION ON RECOVERY/RECYCLING

DISCLAIMER: THE INFORMATION HEREIN WAS OBTAINED FROM SOURCES CONSIDERED TO BE RELIABLE. HOWEVER, THIS INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS OR SUITABILITY FOR CONSUMERS INTENDED USE AND/OR APPLICATION. FOR THIS AND OTHER REASONS, WE ASSUME NO RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT. THIS MSDS WAS PREPARED EXPRESSLY FOR THIS PRODUCT. USE THE MATERIALS ONLY AS DIRECTED. IF THE PRODUCT IS USED AS A COMPONENT OF ANOTHER PRODUCT, THE INFORMATION CONTAINED WITHIN THE MSDS MAY BE APPLICABLE. IF THERE ARE ANY PROBLEMS OR CONCERNS UNDERSTANDING THIS MSDS FORM, PLEASE DIRECT ALL QUESTIONS TO INFOTRAC CHEMICAL RESPONSE 352-323-3500.

NAILITE

4530 N HIATUS ROAD #109
SUNRISE, FL 33351 UNITED STATES
800-222-4472/954-741-2924
800-222-4472/954-741-2924

IN CASE OF EMERGENCY: 1-352-323-3500