

SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	Stylus Gel (including pink versions)	DATE PREPARED:	January 1, 2009
GENERAL USE:	Fingernail overlay resin	SUPPERSEDES:	May 1, 2008
PRODUCT DESCRIPTION:	polyurethane acrylate prepolymer resin blend	TELEPHONE NUMBER:	+1 954 741 2924
		EMERGENCY TELEPHONE N	+1 954 741 2924

MANUFACTURER'S NAME			
Nailite			
ADDRESS		TELEPHONE NUMBER:	
4530 N Hiatus Road #109		+1 954 741 2924	
(CITY, STATE AND POSTAL CODE)		COUNTRY	EMERGENCY TELEPHONE NUMBER:
Sunrise, FL 33351		USA	+1 954 741 2924

SECTION 2 - HAZARDOUS INGREDIENTS

COMPONENTS	% (by weight)	CAS#	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 16)
Polyurthane acrylate prepolymer res	52-70	N/A	N/A	Xi	R-36/38
Polyurethane methacrylate prepolymer resin	25-35	N/A	N/A	Xi	R-36/38
Tripropyleneglycol diacrylate	0-5	42978-66-5	256-032-2	Xi	R-36/38
1-hydroxycyclohexylphenylketone	1-2	947-19-3	213-426-9	none	none
Benzophenone	1-2	119-61-9	204-337-6	none	none
CI77891 (TiO2)	0-0.1	13463-67-7	236-675-5	none	none
CI75470 (carmine red)	0-0.1	1328-60-5	215-527-3	none	none

c) Indicates an employee's skin exposure shall be prevented or reduced to the extent necessary in the circumstances through the use of gloves or other appropriate equipment.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Clear or pigmented liquid. Will support combustion. May cause complications if swallowed. Know allergen upon over exposure in some cases. Avoid skin contact. Inhalation of mist or liquid can cause respiratory irritation. Hazard symbols for the product - see section XV below Risk Phrases - see section XV below

POTENTIAL HEALTH EFFECTS

INHALATION: No significant adverse health effects are expected to occur upon short-term exposure. Prolonged exposure to mists may cause an allergic reaction. Mists are defined as liquids that are in vaporous form. This would not be how the material is designed to be used or applied.

SKIN: No allergic reaction is expected to occur upon short term exposure. Individuals who are known to have allergies to acrylics, acrylic acids, carboxylic acids, epoxy resins or other UV cured products should avoid skin contact.

EYES: No adverse effects are known for this product upon short-term exposure to the eyes. It is best to avoid contact with the eye region and surrounding skin.

INHALATION: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention. There has never been any incidence of any inhalation incidence known to the manufacturer.

SKIN: Remove contaminated clothing and wash contact area with soap and water for 15 minutes. Particular attention should be paid to hair, nose, ears and other areas not easily cleaned. See section 8 . Note to physician: effects can be delayed 24-48 hours.

EYES: Flush with plenty of water for at least 15 minutes and seek medical attention.

INGESTION: If appreciable quantities are swallowed, seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS: Product will support combustion. Products of combustion will include compounds of carbon, nitrogen and oxygen including carbon monoxide.

EXTINGUISHING MEDIA: Carbon dioxide, water fog, dry chemical and chemical foam.

FIRE FIGHTING PROCEDURES: Firefighters must wear a full-face self-contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will cause fire to scatter and spread fire. Fine water spray can be used to keep fire-exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers can explode due to build-up of pressure due to extreme heat.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes, oxides of carbon, nitrogen containing compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WILL SUPPORT COMBUSTION. Do not wash to sanitary sewer. All spills can be polymerized into a plastic with the use of UV light source: sunlight, UV light lamp. If no light source is readily available, use a trowel or shovel to gather the material into a container, transport to a UV light source and polymerize. Polymerized material can be disposed of in accordance with local, state and federal regulations.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use. Protect containers from abuse. Do not expose containers to UV light (including sunlight), peroxides or other free-radical reaction initiators. Do not expose material to temperatures in excess of 60 °C. Do not expose to open flame. This material will support combustion. Keep this material and all chemicals out of the reach of children. Avoid prolonged contact with skin, mucous membranes, eyes, open wounds,

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS:	NIOSH				ACGIH			
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3

EYE PROTECTION: Safety glasses or splash goggles. For large exposure situations, a full-face splash shield is required.			
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station.			
WORK / HYGENIC PRACTICES: Always practice safe workplace habits. Minimize body contact with this as well as all chemicals in general.			
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES			
APPEARANCE AND ODOR Clear or pigmented liquid	VAPOR PRESSURE not applicable		
pH not applicable	SPECIFIC GRAVITY (WATER = 1) 1.1		
BOILING POINT / BOILING RANGE not applicable	SOLUBILITY IN WATER not soluble		
FLASH POINT >212 F / 100 C	VISCOSITY 30,000 cps		
FLAMMABLE LIMITS not applicable	VAPOR DENSITY (AIR = 1) <1		
AUTOIGNITION TEMPERATURE not applicable	EVAPORATION RATE (WATER = 1) not applicable		
SECTION 10 - STABILITY AND REACTIVITY			
STABILITY	STABLE X	UNSTABLE	CONDITIONS TO AVOID: Temperatures over 60 °C, open flame, UV light (including sunlight)
INCOMPATABILITY (MATERIALS TO AVOID): Strong oxidizers, peroxides, UV light sources, sunlight, temperatures over 60 °C and loss of inhibitor.			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of fire, oxides of carbon, oxides of nitrogen, hydrocarbons, fumes and smoke may be produced.			
HAZARDOUS POLYMERIZATION	MAY OCCUR X	WILL NOT OCCUR	CONDITIONS TO AVOID: Temperatures over 60 °C, open flame, UV light (including sunlight)
SECTION 11 - TOXICOLOGICAL INFORMATION			
HAZARDOUS COMPONENTS	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Polyurthane acrylate prepolymer resin	N/A N/A	>2000 skin/rat	n/a
tripropylene glycol diacrylate	42978-66-5 256-032-2	>2000 skin/rat	n/a
1-hydroxycyclohexylphenylketone	947-19-3 213-426-9	>2000 skin/rat	n/a
benzophenone	119-61-9 204-337-6	>2000 skin/rat	n/a
SECTION 12 - ECOLOGICAL INFORMATION			
Biologic Degredation: Biodegradation: n.a. Behavior in environmental compartments: Distribution: log p(o/w): n.a. no bioaccumulation to be expected Ecotoxic effects:		Maximum permissible toxic concentrations: Algal toxicity: Sc. Quadricauda IC5: n.a. Bacterial toxicity: M. aeruginosa EC5: n.a. Protazoa: E. sulcatum EC5: n.a.	

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Polyurethane prepolymer resin	IATA CLASS / Packing Group: Not Regulated
DOT HAZARD CLASS / Packing Group: Not Regulated	IMDG HAZARD CLASS: Not Regulated
REFERENCE: Not Applicable	RID / ADR Dangerous Goods Code: Not Regulated
UN/NA ID NUMBER: None	UN TDG Class/ Pack Group: Not Regulated
LABEL: None	Hazard Identification Number (HIN): Not Regulated
HAZARD SYMBOLS: None	

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100-177, IMDG, IATA, EU, United Nations TDG and WHIMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act)

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act)

311 / 312 Hazard Categories: None

313 Reportable Ingredients: None

CERCLA (USA - Comprehensive Response and Liability Act) : None

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There is nothing known to the State of California to cause cancer or reproductive toxicity.

CFR (Canadian Controlled Products Regulations):

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains information required by the Controlled Products Regulations. WHIMIS Classification: None

IDL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)


Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

WGK Water Index: 1

VbK Index: AIII

RISK PHRASES:	SYMBOL(S) REQUIRED FOR LABEL	SAFETY PHRASES:
R-36/38 Irritating to eyes and skin	IRRITANT 	S-24/25 Avoid contact with skin and eyes S-26 In case of contact with eyes, rinse immediately S-41 In case of fire and/or explosion, do not breathe fumes

EU DIRECTIVES: DIRECTIVE 91/155/EEC amended by Directive 93/112/EEC and Directive 2001/58/EC : Safety Data Sheets
 Dangerous preparations: Directive 1999/45/EC amended by Directive 2001/60/EC - OJEC L226 - 22/08/2001 and Directive 2006/08/EC - 24/01/2006.

Commission Directive 2004/73/EC of 29 April 2004 adapting to technical progress for the 29th time Council Directive 67/548/EEC on the approximation of the laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances (Official Journal L216 - 16/06/2004).